




## OUTDOOR



**Weather-resistant  
and non-slip**



Granuflex's circular rubber tiles and drainage solutions are virtually impervious to the weather, making them ideally suited for outdoor use. Rubber has an excellent and natural damping effect, so people will be less likely to injure themselves in the event of a fall. Moreover, its non-slip properties are an obvious boost to safety.

And the maintenance of all circular tiles for outdoor use couldn't be easier. A brush, water and some non-aggressive soap and, in no time at all, they'll be as good as new.

## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

**400x400MM**  
221ZWA025BL040XX



## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

**500x500MM**  
221ZWA025BL050XX



## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

**1,000x1,000MM**  
221ZWA025BL100XX



## ARTIFICIAL GRASS GALLERY TILE NATURAL LOOK 50MM

Tile with a long-fibred artificial grass top layer. Without pin/hole connection. Its high quality artificial grass lends it a very natural appearance.

**500x500MM**  
230KGR030B4050ET



## TILE SUPPORT 10MM

Tile supports are typically used to protect the bituminous layer on roof terraces/gardens and flat roofs. They are the perfect solution for supporting stone or concrete tiles. Packaged per 144 pieces.

**100x100MM**  
(Other sizes are available on request)  
228ZWA010AA100GR



## OPTI-DRAIN DRAINAGE MAT

A mat that is used to control drainage and is available in both horizontal and vertical configurations. Equipped with a handy interlocking system and geo-textile layer.

**20,000x1,200MM**  
230ZWA009HD120XX



### CHARACTERISTICS



DRAINAGE



ANTI-SLIP



SUSTAINABLE

### COLOURS



BLACK

GREY

GREEN

RED

### GUARANTEE

3 YEARS

GRANUFLEX® RUBBER TILES COMPLY WITH THE REQUIREMENTS OF REACH REGULATION EU 1907/2006. IN ACCORDANCE WITH ENTRY 50 ANNEX XVII OF THIS REACH REGULATION, THIS PRODUCT SHOULD NOT BE USED IN SITUATIONS IN WHICH FREQUENT SKIN CONTACT IS POSSIBLE OR AS A SURFACE ON WHICH CHILDREN REGULARLY PLAY.

## OUTDOOR STANDARD 30MM

For outdoor fitness areas, basic duty. Coarse granulate structure. Top side flat and profiled base.

**1,000x1,000MM**  
226ZWA030M4100FI



## OUTDOOR XTREME 43MM

For outdoor fitness areas, basic duty. Coarse granulate structure. Top side flat and profiled base.

**1,000x1,000MM**  
226ZWA043M4100FI



### CHARACTERISTICS



DRAINAGE



HYGIENIC



ROBUST



SOUND INSULATION

### COLOURS



BLACK

GREY

GREEN

RED

### GUARANTEE

2 YEARS

# PUBLIC SPACES

## PLAYGROUND TILE ESP PIN/HOLE 40MM

Rubber tile for a free-fall height (HIC) up to 1.27m. HIC rating in combination with 30mm High Impact Underlay: 2.32m.

500x500MM  
223ZWA040M3050YES



## PLAYGROUND TILE ESP PIN/HOLE 45MM

Rubber tile for a free-fall height (HIC) up to 1.29m. HIC rating in combination with 30mm High Impact Underlay: 2.52m.

500x500MM  
223ZWA045M3050YES



## PLAYGROUND TILE ESP PIN/HOLE 55MM

Rubber tile for a free-fall height (HIC) up to 1.52m. HIC rating in combination with 30mm High Impact Underlay: 2.93m.

500x500MM  
223ZWA055M3050YES



## EPDM TILE 30MM

Rubber tile for a free-fall height (HIC) up to 1.05m.

500x500MM  
2245015030AA050XX



## EPDM TILE 40MM

Rubber tile for a free-fall height (HIC) up to 1.40m.

500x500MM  
2245015040AA050XX



## EPDM TILE 45MM

Rubber tile for a free-fall height (HIC) up to 1.55m.

500x500MM  
2245015045AA050XX



## PLAYGROUND TILE ESP PIN/HOLE 65MM

Rubber tile for a free-fall height (HIC) up to 2.01m. HIC rating in combination with 30mm High Impact Underlay: 3m.

500x500MM  
223ZWA065M3050YES



## HIGH IMPACT UNDERLAY 30MM

Underlay with excellent damping properties. Use in combination with Granuflex rubber tiles.

1,500x2,000MM  
230WIT030B4200FS



## EPDM TILE 65MM

Rubber tile for a free-fall height (HIC) up to 2.15m.

500x500MM  
2245015065AA050XX



## EPDM TILE 100MM

Rubber tile for a free-fall height (HIC) up to 3.0m.

500x500MM  
2245015100AA050XX



## ARTIFICIAL GRASS GALLERY TILE NATURAL LOOK 50MM

Rubber tile with high-quality artificial grass for a genuinely natural appearance. Free-fall height (HIC) up to 1.08m. HIC value in combination with 30mm High Impact Underlay: 2.30m.

500x500MM  
230KGR030B4050ET



## RUBBER GRANULATE 2.0-3.5MM

Rubber granulate of this grade is optimally suited for the creation of a durable damping foundation beneath seamless (rubber) playground floors.

333ZWA020035B1000N



## RUBBER ADHESIVE IN A CARTRIDGE

Perfect for gluing, mounting and sealing. Remains elastic, tensile strength (DIN 53404) 27kg/cm<sup>2</sup>.

230XXX010FIXXXGJ



### CHARACTERISTICS



### COLOURS



### GUARANTEE



### CERTIFICATION

HIC EN-1177



GRANUFLEX® PLAYGROUND-, ECOSAFEPLAY-, AND EPDM TILES COMPLY WITH THE REQUIREMENTS OF REACH REGULATION EU 1907/2006. IN ACCORDANCE WITH ENTRY 50 ANNEX XVII OF THIS REACH REGULATION, THIS PRODUCT CAN BE USED IN SITUATIONS IN WHICH FREQUENT SKIN CONTACT IS POSSIBLE OR AS A SURFACE ON WHICH CHILDREN REGULARLY PLAY.

### CHARACTERISTICS



### COLOURS



### GUARANTEE



### CERTIFICATION

HIC EN-1177



GRANUFLEX® PLAYGROUND-, ECOSAFEPLAY-, AND EPDM TILES COMPLY WITH THE REQUIREMENTS OF REACH REGULATION EU 1907/2006. IN ACCORDANCE WITH ENTRY 50 ANNEX XVII OF THIS REACH REGULATION, THIS PRODUCT CAN BE USED IN SITUATIONS IN WHICH FREQUENT SKIN CONTACT IS POSSIBLE OR AS A SURFACE ON WHICH CHILDREN REGULARLY PLAY.

## SAFETY TILE 20 | 30 | 43 | 55MM

Rubber tile for free-fall heights of 0.7 to 1.6m.

500x500MM  
223ZWA020AA050XX



## SAFETY TILE 30 | 40 | 45 | 55 | 65 | 75 | 85 | 100MM

Rubber tile for free-fall heights of 0.7 to 3.0m.

1,000x1,000MM  
223ZWA085AA100XX



## SAFETY TILE WITH PIN/HOLE 30 | 40 | 45 | 55 | 65 | 75 | 85 | 100MM

Rubber tile for free-fall heights of 0.9 to 2.6m.

500x500MM  
223ZWA030M3050XX



## HALF SAFETY TILE WITH PIN/HOLE

To be combined with Granuflex pin/hole tiles.

500x250MM  
223ZWA100M3S25XX



## BEVELLED PIN/HOLE TILE

To be combined with Granuflex pin/hole tiles.

500x500MM  
223ZWA030V6050XX



## CORNER PIN/HOLE TILE

To be combined with Granuflex pin/hole tiles.

500x500MM  
223ZWA030V7050XX




## HIGH IMPACT UNDERLAY 30MM

Underlay with excellent damping properties. Use in combination with Granuflex rubber tiles.

1,500x2,000MM  
230WIT030B4200FS



## CHARACTERISTICS



## COLOURS



## GUARANTEE



## CERTIFICATION



GRANUFLEX® SAFETY TILES COMPLY WITH THE REQUIREMENTS OF REACH REGULATION EU 1907/2006. IN ACCORDANCE WITH ENTRY 50 ANNEX XVII OF THIS REACH REGULATION, THIS PRODUCT SHOULD NOT BE USED IN SITUATIONS IN WHICH FREQUENT SKIN CONTACT IS POSSIBLE OR AS A SURFACE ON WHICH CHILDREN REGULARLY PLAY. SHOULD THIS BE NECESSARY, GRANUFLEX ECOSAFEPLAY PLAYGROUND TILES ARE A SUITABLE SOLUTION.

## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

400x400MM  
221ZWA025BL040XX



## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

500x500MM  
221ZWA025BL050XX



## HOBBY TILE 25MM

Rubber tile suitable for many applications. A terrace can be laid on a balcony, roof, patio and/or garden in no time at all. And the installation of a walkway or damping surface is both quick and easy.

1,000x1,000MM  
221ZWA025BL100XX



## SAFETY TILE 43MM

Rubber tile for creating an optimally damping substructure. Also suitable for laying a terrace on which garden furniture is to be placed. The tile's special open structure allows rain to easily drain through it.

1,000x1,000MM  
223ZWA043BL100XX



## ARTIFICIAL GRASS GALLERY TILE NATURAL LOOK 50MM

Tile with a long-fibred artificial grass top layer. Without pin/hole connection. Its high quality artificial grass lends it a very natural appearance.

500x500MM  
230KGR030B4050ET



## CHARACTERISTICS



## COLOURS



## GUARANTEE



GRANUFLEX® RUBBER TILES COMPLY WITH THE REQUIREMENTS OF REACH REGULATION EU 1907/2006. IN ACCORDANCE WITH ENTRY 50 ANNEX XVII OF THIS REACH REGULATION, THIS PRODUCT SHOULD NOT BE USED IN SITUATIONS IN WHICH FREQUENT SKIN CONTACT IS POSSIBLE OR AS A SURFACE ON WHICH CHILDREN REGULARLY PLAY.

# LADDER MATS

## LADDER MAT BASIC 56MM

Granuflex ladder mats have been designed and developed so that they minimise the risk of a ladder slipping. Suitable for ladders up to 95cm wide.

1,000x250MM  
229ZWAXXB1L25XX



## LADDER MAT PRO 56MM

Granuflex ladder mats have been designed and developed so that they minimise the risk of a ladder slipping. Suitable for ladders up to 125cm wide with handle.

1,300x300MM  
229ZWAXXB1L30XX



### CHARACTERISTICS



SAFE



ANTI-SLIP



100%  
RECYCLABLE



SOUND  
INSULATION

### COLOURS



### GUARANTEE

3 YEARS

### CERTIFICATION

SLIP RESISTANCE NEN 2484

